

DEGREE SEQUENCES OF MONOCORE GRAPHS

ALLAN BICKLE

Department of Mathematics
Dordt College 498 4th Ave NE Sioux Center
Iowa, USA

e-mail: allan.bickle@dordt.edu

Abstract

A k -monocore graph is a graph which has its minimum degree and degeneracy both equal to k . Integer sequences that can be the degree sequence of some k -monocore graph are characterized as follows. A nonincreasing sequence of integers d_1, \dots, d_n is the degree sequence of some k -monocore graph G , $0 \leq k \leq n - 1$, if and only if $k \leq d_i \leq \min\{n - 1, k + n - i\}$ and $\sum d_i = 2m$, where m satisfies $\lceil \frac{k \cdot n}{2} \rceil \leq m \leq k \cdot n - \binom{k+1}{2}$.

Keywords: monocore graph, degeneracy, degree sequence.

2010 Mathematics Subject Classification: 05C75.

REFERENCES

- [1] M. Altaf-Ul-Amin, K. Nishikata, T. Koma, T. Miyasato, Y. Shinbo, M. Arifuzzaman, C. Wada, M. Maeda, *et al.*, *Prediction of protein functions based on k-cores of protein-protein interaction networks and amino acid sequences*, Genome Informatics **14** (2003) 498–499.
- [2] J. Alvarez-Hamelin, L. Dall'Asta, A. Barrat, A. Vespignani, *k-core decomposition: a tool for the visualization of large scale networks*, Adv. Neural Inf. Process. Syst. **18** (2006) 41.
- [3] G. Bader, C. Hogue, *An automated method for finding molecular complexes in large protein interaction networks*, BMC Bioinformatics **4** (2003). doi:10.1186/1471-2105-4-2
- [4] V. Batagelj and M. Zaversnik, *An O(m) algorithm for cores decomposition of networks*. <http://vlado.fmf.uni-lj.si/pub/networks/doc/cores/cores.pdf>. (2002) Last accessed November 25, 2011.
- [5] A. Bickle, *The k-cores of a Graph* (Ph.D. Dissertation, Western Michigan University, 2010).
- [6] A. Bickle, *Structural results on maximal k-degenerate graphs*, Discuss. Math. Graph Theory **32** (2012) 659–676. doi:10.7151/dmgt.1637
- [7] A. Bickle, *Cores and shells of graphs*, Math. Bohemica **138** (2013) 43–59.
- [8] B. Bollobas, *Extremal Graph Theory* (Academic Press, 1978).
- [9] M. Borowiecki, J. Ivančo, P. Mihók and G. Semanišin, *Sequences realizable by maximal k-degenerate graphs*, J. Graph Theory **19** (1995) 117–124. doi:10.1002/jgt.3190190112
- [10] G. Chartrand and L. Lesniak, *Graphs and Digraphs*, (4th Ed.) (CRC Press, 2005).
- [11] S. Dorogovtsev, A. Goltsev and J. Mendes, *k-core organization of complex networks*, Phys. Rev. Lett. **96** (2006).
- [12] Z. Filáková, P. Mihók and G. Semanišin., *A note on maximal k-degenerate graphs*, Math. Slovaca **47** (1997) 489–498.
- [13] M. Gaertler and M. Patrignani, *Dynamic analysis of the autonomous system graph*, Proc. 2nd International Workshop on Inter-Domain Performance and Simulation (2004) 13–24.
- [14] D.R. Lick and A.T. White, *k-degenerate graphs*, Canad. J. Math. **22** (1970) 1082–1096. doi:10.4153/CJM-1970-125-1
- [15] T. Luczak, *Size and connectivity of the k-core of a random graph*, Discrete Math. **91** (1991) 61–68. doi:10.1016/0012-365X(91)90162-U

- [16] J. Mitchem, *Maximal k-degenerate graphs*, Util. Math. **11** (1977) 101–106.
- [17] S.B. Seidman, *Network structure and minimum degree*, Soc. Networks **5** (1983) 269–287.
doi:10.1016/0378-8733(83)90028-X
- [18] J.M.S. Simões-Pereira, *A survey of k-degenerate graphs*, Graph Theory Newsletter **5** (1976) 1–7.
- [19] D. West, Introduction to Graph Theory, (2nd Ed.) (Prentice Hall, 2001).
- [20] S. Wuchty and E. Almaas, *Peeling the yeast protein network*, Proteomics **5** (2005) 444–449.
doi:10.1002/pmic.200400962

Received 9 January 2013

Revised 9 July 2013

Accepted 8 August 2013