

COMPLETELY INDEPENDENT SPANNING TREES IN (PARTIAL) k -TREES

MASAYOSHI MATSUSHITA¹, YOTA OTACHI²

AND

TORU ARAKI¹

¹ Department of Computer Science
Gunma University, Kiryu
Gunma 376-8515 Japan

² School of Information Science
Japan Advanced Institute of Science and Technology
Asahidai 1-1, Nomi, Ishikawa 923-1292, Japan

e-mail: otachi@jaist.ac.jp
arakit@gunma-u.ac.jp

Abstract

Two spanning trees T_1 and T_2 of a graph G are completely independent if, for any two vertices u and v , the paths from u to v in T_1 and T_2 are internally disjoint. For a graph G , we denote the maximum number of pairwise completely independent spanning trees by $cist(G)$. In this paper, we consider $cist(G)$ when G is a partial k -tree.

First we show that $\lceil k/2 \rceil \leq cist(G) \leq k - 1$ for any k -tree G . Then we show that for any $p \in \{\lceil k/2 \rceil, \dots, k - 1\}$, there exist infinitely many k -trees G such that $cist(G) = p$. Finally we consider algorithmic aspects for computing $cist(G)$. Using Courcelle's theorem, we show that there is a linear-time algorithm that computes $cist(G)$ for a partial k -tree, where k is a fixed constant.

Keywords: completely independent spanning trees, partial k -trees.

2010 Mathematics Subject Classification: 05C05, 05C38.

REFERENCES

- [1] T. Araki, *Dirac's condition for completely independent spanning trees*, J. Graph Theory **77** (2014) 171–179.
doi:10.1002/jgt.21780

- [2] S. Arnborg and A. Proskurowski, *Linear time algorithms for NP-hard problems restricted to partial k-trees*, Discrete Appl. Math. **23** (1989) 11–24.
doi:10.1016/0166-218X(89)90031-0
- [3] H.L. Bodlaender, *A partial k-arboretum of graphs with bounded treewidth*, Theoret. Comput. Sci. **209** (1998) 1–45.
doi:10.1016/S0304-3975(97)00228-4
- [4] H.L. Bodlaender, F.V. Fomin, P.A. Golovach, Y. Otachi and E.J. van Leeuwen, *Parameterized complexity of the spanning tree congestion problem*, Algorithmica **64** (2012) 85–111.
doi:10.1007/s00453-011-9565-7
- [5] H.L. Bodlaender and A.M.C.A. Koster, *Combinatorial optimization on graphs of bounded treewidth*, Comput. J. **51** (2008) 255–269.
doi:10.1093/comjnl/bxm037
- [6] B. Courcelle, *The monadic second-order logic of graphs III: tree-decompositions, minors and complexity issues*, Theor. Inform. Appl. **26** (1992) 257–286.
- [7] T. Hasunuma, *Completely independent spanning trees in the underlying graph of a line digraph*, Discrete Math. **234** (2001) 149–157.
doi:10.1016/S0012-365X(00)00377-0
- [8] T. Hasunuma, *Completely independent spanning trees in maximal planar graphs* in: Proceedings of 28th Graph Theoretic Concepts of Computer Science (WG 2002), LNCS **2573**, Springer-Verlag Berlin (2002) 235–245.
doi:10.1007/3-540-36379-3_21
- [9] T. Hasunuma and C. Morisaka, *Completely independent spanning trees in torus networks*, Networks **60** (2012) 59–69.
doi:10.1002/net.20460
- [10] P. Hliněný, S. Oum, D. Seese and G. Gottlob, *Width parameters beyond tree-width and their applications*, Comput. J. **51** (2008) 326–362.
doi:10.1093/comjnl/bxm052
- [11] F. Péterfalvi, *Two counterexamples on completely independent spanning trees*, Discrete Math. **312** (2012) 808–810.
doi:10.1016/j.disc.2011.11.015

Received 24 April 2014
Revised 8 August 2014
Accepted 8 August 2014