

$\mathbb{Z}_2 \times \mathbb{Z}_2$ -CORDIAL CYCLE-FREE HYPERGRAPHS

SYLWIA CICHACZ, AGNIESZKA GÖRLICH

*AGH University of Science and Technology
al. A. Mickiewicza 30, 30–059 Kraków, Poland*

e-mail: cichacz@agh.edu.pl
forys@agh.edu.pl

AND

ZSOLT TUZA

*Alfréd Rényi Institute of Mathematics
Hungarian Academy of Sciences
H-1053 Budapest, Reáltanoda u. 13–15
and*

*Department of Computer Science and Systems Technology
University of Pannonia
H-8200 Veszprém, Egyetem u. 10, Hungary*

e-mail: tuza@dcs.uni-pannon.hu

Abstract

Hovey introduced A -cordial labelings as a generalization of cordial and harmonious labelings [7]. If A is an Abelian group, then a labeling $f: V(G) \rightarrow A$ of the vertices of some graph G induces an edge labeling on G ; the edge uv receives the label $f(u) + f(v)$. A graph G is A -cordial if there is a vertex-labeling such that (1) the vertex label classes differ in size by at most one and (2) the induced edge label classes differ in size by at most one.

The problem of A -cordial labelings of graphs can be naturally extended for hypergraphs. It was shown that not every 2-uniform hypertree (i.e., tree) admits a $\mathbb{Z}_2 \times \mathbb{Z}_2$ -cordial labeling [8]. The situation changes if we consider p -uniform hypertrees for a bigger p . We prove that a p -uniform hypertree is $\mathbb{Z}_2 \times \mathbb{Z}_2$ -cordial for any $p > 2$, and so is every path hypergraph in which all edges have size at least 3. The property is not valid universally in the class of hypergraphs of maximum degree 1, for which we provide a necessary and sufficient condition.

Keywords: V_4 -cordial graph, hypergraph, labeling of hypergraph, hypertree.

2010 Mathematics Subject Classification: 05C65, 05C78.

REFERENCES

- [1] I. Cahit, *Cordial graphs: a weaker version of graceful and harmonious graphs*, Ars Combin. **23** (1987) 201–207.
- [2] N. Cairnie and K. Edwards, *The computational complexity of cordial and equitable labelling*, Discrete Math. **216** (2000) 29–34.
[https://doi.org/10.1016/S0012-365X\(99\)00295-2](https://doi.org/10.1016/S0012-365X(99)00295-2)
- [3] S. Cichacz, A. Gölich and Zs. Tuza, *Cordial labeling of hypertrees*, Discrete Math. **313** (2013) 2518–2524.
<https://doi.org/10.1016/j.disc.2013.07.025>
- [4] K. Driscoll, E. Krop and M. Nguyen, *All trees are six-cordial*, Electron. J. Graph Theory Appl. **5** (2017) 21–35.
<https://doi.org/10.5614/ejgta.2017.5.1.3>
- [5] J.A. Gallian, *A dynamic survey of graph labeling*, Electron. J. Combin. **17** (2010) #DS6.
- [6] I.M. Gessel and L.H. Kalikow, *Hypergraphs and a functional equation of Bouwkamp and De Bruijn*, J. Comb. Theory Ser. A **110** (2005) 275–289.
<https://doi.org/10.1016/j.jcta.2004.11.002>
- [7] M. Hovey, *A-cordial graphs*, Discrete Math. **93** (1991) 183–194.
[https://doi.org/10.1016/0012-365X\(91\)90254-Y](https://doi.org/10.1016/0012-365X(91)90254-Y)
- [8] O. Pechenik and J. Wise, *Generalized graph cordiality*, Discuss. Math. Graph Theory **32** (2012) 557–567.
<https://doi.org/10.7151/dmgt.1626>
- [9] M. Tuczyński, P. Wenus and K. Węsek, *On cordial hypertrees* (2017).
arXiv:1711.06294

Received 15 September 2018

Revised 5 April 2019

Accepted 5 April 2019